



BUILDING CODE COMPLIANCE OFFICE (BCCO)
PRODUCT CONTROL DIVISION

MIAMI-DADE COUNTY, FLORIDA
METRO-DADE FLAGLER BUILDING

140 WEST FLAGLER STREET, SUITE 1603
MIAMI, FLORIDA 33130-1563
(305) 375-2901 FAX (305) 375-2908

www.miamidade.gov

NOTICE OF ACCEPTANCE (NOA)

Poma Corporation
9040 Belvedere Road
West Palm Beach, Florida 33411

SCOPE:

This NOA is being issued under the applicable rules and regulations governing the use of construction materials. The documentation submitted has been reviewed by Miami-Dade County Product Control Division and accepted by the Board of Rules and Appeals (BORA) to be used in Miami Dade County and other areas where allowed by the Authority Having Jurisdiction (AHJ).

This NOA shall not be valid after the expiration date stated below. The Miami-Dade County Product Control Division (In Miami Dade County) and/or the AHJ (in areas other than Miami Dade County) reserve the right to have this product or material tested for quality assurance purposes. If this product or material fails to perform in the accepted manner, the manufacturer will incur the expense of such testing and the AHJ may immediately revoke, modify, or suspend the use of such product or material within their jurisdiction. BORA reserves the right to revoke this acceptance, if it is determined by Miami-Dade County Product Control Division that this product or material fails to meet the requirements of the applicable building code.

This product is approved as described herein, and has been designed to comply with the High Velocity Hurricane Zone of the Florida Building Code.

DESCRIPTION: Extruded Aluminum Bahama Shutter

APPROVAL DOCUMENT: Drawing No. 07-301, titled "Bahama Shutter", sheets 1 through 3 of 3, prepared by Thornton Tomasetti, dated February 07, 2007, last revision #0 dated February 07, 2007, signed & sealed by J. W. Knezevich, P.E., bearing Miami-Dade County Product Control Revision stamp with the Notice of Acceptance number and expiration date by the Miami-Dade County Product Control Division.

MISSILE IMPACT RATING: Large and Small Missile Impact

LABELING: Each unit shall bear a permanent label with the manufacturer's name or logo, city, state and the following statement: "Miami-Dade County Product Control Approved", unless otherwise noted herein.

RENEWAL of this NOA shall be considered after a renewal application has been filed and there has been no change in the applicable building code negatively affecting the performance of this product.

TERMINATION of this NOA will occur after the expiration date or if there has been a revision or change in the materials, use, and/or manufacture of the product or process. Misuse of this NOA as an endorsement of any product, for sales, advertising or any other purposes shall automatically terminate this NOA. Failure to comply with any section of this NOA shall be cause for termination and removal of NOA.

ADVERTISEMENT: The NOA number preceded by the words Miami-Dade County, Florida, and followed by the expiration date may be displayed in advertising literature. If any portion of the NOA is displayed, then it shall be done in its entirety.

INSPECTION: A copy of this entire NOA shall be provided to the user by the manufacturer or its distributors and shall be available for inspection at the job site at the request of the Building Official.

This NOA **revises & renews** NOA # 00-0822.09 and consists of this page 1, evidence submitted page E-1 as well as approval document mentioned above.

The submitted documentation was reviewed by **Helmy A. Makar, P.E., M.S.**



Helmy A. Makar
03/15/2007

NOA No 04-1020.01
Expiration Date: 03/15/2012
Approval Date: 03/15/2007
Page 1

Poma Corporation

NOTICE OF ACCEPTANCE: EVIDENCE SUBMITTED

1. EVIDENCE SUBMITTED UNDER PREVIOUS APPROVAL #00-0822.09

A. DRAWINGS

1. *Drawing No. 99-262, titled "Bahama Shutter", prepared by Knezevich & Associates, Inc., dated July 24, 2000, last revision #1 dated November 6, 2000, sheets 1 through 3 of 3, signed and sealed by V. J. Knezevich, P.E.*

B. TESTS

1. *Test report on Large Missile Impact Test, Cyclic Wind Pressure Test, and Uniform Static Air Pressure Test of Bahama Shutters, prepared by Construction Testing Corporation, Report No. 00-026, dated 07/25/2000, signed and sealed by Christopher G. Tyson, P.E.*

C. CALCULATIONS

1. *Comparative analysis and Anchor calculation, dated August 3, 2000, sheets 1 through 6, prepared by Knezevich & Associates, Inc., signed and sealed by V. J. Knezevich, P.E.*

D. MATERIAL CERTIFICATIONS

1. *Customer Extrusions by Metal Industries, Inc.*
2. *Tensile Test Report issued by Certified Testing Laboratories, dated August 28, 2000, Report No. CTL-797F.*

2. NEW EVIDENCE SUBMITTED

A. DRAWINGS

1. *Drawing No. 07-301, titled "Bahama Shutter", sheets 1 through 3 of 3, prepared by Thornton Tomasetti, dated February 07, 2007, last revision #0 dated February 07, 2007, signed & sealed by J. W. Knezevich, P.E.,*

B. TESTS

1. *None.*

C. CALCULATIONS


1. *Revised Anchor analysis and calculations dated February 04, 2007, 14 Pages, prepared by Thornton Tomasetti, signed and sealed by John W. Knezevich, P.E. on Februar 04, 2007.*

D. QUALITY ASSURANCE

1. *By Miami-Dade County Building Code Compliance Office.*

E. MATERIAL CERTIFICATIONS

1. *None.*




Helmy A. Makar, P. E., M.S.
Product Control Examiner
NOA No 04-1020.01
Expiration Date: 03/15/2012
Approval Date: 03/15/2007

Print Information: P:\F11\Projects\Kk7301.00\Drawings\RO-sub\07-301-01.dwg MCantu 02/07/2007 12:19:13pm 02/07/07 12:19


GENERAL NOTES:

1. THESE PRODUCT EVALUATION DOCUMENTS REPRESENT A SHUTTER SYSTEM ANALYZED WITH THE PROVISION SET FOR THE ISSUANCE OF A NOTICE OF ACCEPTANCE (NOA) BY MIAMI-DADE COUNTY PRODUCT CONTROL DIVISION FOR THE HIGH VELOCITY HURRICANE ZONE (HVHZ) OF THE FLORIDA BUILDING CODE 2004 WITH 2005 & 2006 SUPPLEMENT.
2. NO INCREASE IN ALLOWABLE STRESS HAS BEEN USED IN THE DESIGN OF THIS PRODUCT. WIND LOAD DURATION FACTOR $C_d = 1.6$ WAS USED FOR WOOD SCREW DESIGN.
3. DETERMINE THE POSITIVE AND NEGATIVE DESIGN LOADS TO USE WHEN REFERENCING THESE DOCUMENTS IN ACCORDANCE WITH THE GOVERNING CODE AND GOVERNING WIND VELOCITY. FOR WIND LOAD CALCULATIONS IN ACCORDANCE WITH ASCE 7-02, A DIRECTIONALITY FACTOR OF $K_d = 0.85$ SHALL BE USED.
4. THESE PRODUCT EVALUATION DOCUMENTS ARE GENERIC AND DO NOT INCLUDE INFORMATION FOR SITE-SPECIFIC APPLICATION OF THIS SHUTTER SYSTEM.
5. USE OF THESE PRODUCT EVALUATION DOCUMENTS SHALL COMPLY WITH CHAPTER 61G15-23 OF THE FLORIDA ADMINISTRATIVE CODE.
6. THESE PRODUCT EVALUATION DOCUMENTS ARE INTENDED FOR USE ONLY BY A LICENSED CONTRACTOR, PROFESSIONAL ENGINEER OR REGISTERED ARCHITECT AND ARE SUITABLE TO BE APPLIED BY THE CONTRACTOR PROVIDED THE CONTRACTOR DOES NOT DEVIATE FROM THE CONDITIONS DETAILED HEREIN AND THE CONTRACTOR VERIFIES THAT THE EXISTING STRUCTURE DOES NOT DEVIATE IN EITHER FORM OR MATERIAL FROM THE STRUCTURAL SUBSTRATES DETAILED HEREIN. CONTRACTOR SHALL VERIFY EXISTING STRUCTURE CAN WITHSTAND SUPERIMPOSED LOAD OF SHUTTER.
7. ANY MODIFICATIONS OR ADDITIONS TO THESE PRODUCT EVALUATION DOCUMENTS WILL VOID THE PRODUCT EVALUATION DOCUMENTS.
8. WHEN THE SITE CONDITIONS DEVIATE FROM THESE PRODUCT EVALUATION DOCUMENTS, THE BUILDING OFFICIAL MAY ELECT ONE OF THE FOLLOWING OPTIONS:
 - A) REQUIRE THAT SITE SPECIFIC DOCUMENTS BE PREPARED, SIGNED, DATED AND SEALED BY A LICENSED ENGINEER OR REGISTERED ARCHITECT, WHICH DETAIL AND JUSTIFY THE DEVIATION. SAID DOCUMENTS SHALL BE SUBMITTED TO THE PRODUCT ENGINEER FOR REVIEW AS A CONDITION TO THE BUILDING OFFICIAL GRANTING HIS/HER APPROVAL.
 - B) REQUIRE THAT A ONE-TIME SITE SPECIFIC APPROVAL BE APPLIED FOR AND SECURED FROM THE MIAMI-DADE COUNTY PRODUCT CONTROL DIVISIONWHEN THE SITE CONDITION DEVIATIONS OCCUR WITHIN THE HIGH VELOCITY HURRICANE ZONE AREAS, ONLY OPTION "B" SHALL BE ACCEPTED BY THE BUILDING OFFICIAL.
9. THE DETAILS AND SPECIFICATIONS SHOWN HEREIN REPRESENT THE PRODUCTS TESTED FOR IMPACT, CYCLIC AND UNIFORM STATIC AIR PRESSURE TESTING IN CONFORMANCE WITH MIAMI-DADE COUNTY PROTOCOLS PA201, 202, AND 203 WITH DESIGN LOADS AS FOLLOWS:
 - A) OPEN POSITION INSTALLATIONS
 - NON-HURRICANE, SHADE CONDITION
 - POSITIVE DESIGN LOAD: 45.1 P.S.F.
 - NEGATIVE DESIGN LOAD: 45.1 P.S.F.
 - B) CLOSED POSITION INSTALLATIONS
 - HURRICANE SHUTTER CONDITION
 - POSITIVE DESIGN LOAD: 97.0 P.S.F.
 - NEGATIVE DESIGN LOAD: 97.0 P.S.F.
 - MIN. SEPARATION FROM GLASS: 3-9/16"
10. EACH SHUTTER ASSEMBLY SHALL BE PERMANENTLY LABELED AS FOLLOWS:


POMA CORPORATION
WEST PALM BEACH, FLORIDA
MIAMI-DADE COUNTY PRODUCT CONTROL APPROVED
11. ALL EXTRUSIONS SHALL BE 6063-T6 ALUMINUM ALLOY, U.O.N.
12. ALL SCREWS, BOLTS AND WASHERS TO BE 2024-T4 ALUMINUM ALLOY OR 300 SERIES STAINLESS STEEL WITH A 60 K.S.I. MINIMUM TENSILE STRENGTH. ALL POP RIVETS SHALL BE 3/16" DIAMETER 5052 ALUMINUM ALLOY.
13. THIS SHUTTER SHALL BE PROVIDED WITH A PERMANENT LABEL INSTRUCTING THE OWNER OR TENANT TO CLOSE AND FASTEN THE SHUTTER TO THE WALL DURING PERIODS OF TIME AS ARE DESIGNATED BY THE U.S. WEATHER BUREAU AS BEING HURRICANE WARNING OR ALERT.




① **"H" TUBE**
SCALE: HALF SCALE




② **JAMB**
SCALE: HALF SCALE




③ **DOUBLE JAMB W/ INSERT**
SCALE: HALF SCALE





④ **FEMALE HINGE**
SCALE: HALF SCALE



⑤ **MALE HINGE**
SCALE: HALF SCALE




⑥ **CAMEL BACK HINGE**
SCALE: HALF SCALE




NOTE: KEYHOLE ACCEPTABLE IN ALL BUT ONE HOLE. PROVIDE ONE 5/16" ϕ HOLE FOR FASTENING, TYPICAL ALL Z BARS.


7a **"Z" BAR (4-1/2" LONG)**
7b **"Z" BAR (7" LONG)**
SCALE: HALF SCALE




⑧ **STARTER BLADE**
SCALE: HALF SCALE




⑨ **STANDARD 2 LOUVER BLADE**
SCALE: HALF SCALE



⑩ **STANDARD 3 LOUVER BLADE**
SCALE: HALF SCALE



⑪ **CLOSURE STRIP**
SCALE: HALF SCALE



⑫ **INSERT**
SCALE: HALF SCALE

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 04-1020-01
Expiration Date 03/15/2012
By *Helene A. Knezevich*
Miami Dade Product Control
Division


Thornton Tomasetti
330 N. Andrews Ave., Suite 450 • Ft. Lauderdale, FL 33301
T 954.522.3690 • F 954.522.3691 • COA # 7519
Website: www.ThorntonTomasetti.com
Copyright © 2007 Thornton Tomasetti, Inc.

BAHAMA SHUTTER
Poma Corporation
9040 Belvedere Road
West Palm Beach, FL 33411
Tel: (561) 790-5799 • Fax (561) 792-9281


J.W. Knezevich
Professional Engineer
FL License No.: PE 0041961

FEB 07 2007


revisions		description
no.	date	by
1	02/07/2007	NW
PREVIOUSLY DRAWING NO. 99-262		
date 02/07/2007		
scale AS NOTED	drawn by MCR	
design by NW	checked by VJK	
drawing no. 07-301		
sheet 1 of 3		




A **TYPICAL ELEVATION (CLOSED POSITION)**
SCALE: 3/8" = 1' - 0"




B **TYPICAL SIDE VIEW (OPEN POSITION)**
SCALE: 3/8" = 1' - 0"




C **HINGE CONNECTION AND LOUVER TO TOP RAIL DETAIL**
SCALE: HALF SCALE



D **SUPPORT PIPE AT CAMEL BACK HINGE TO WALL**
SCALE: HALF SCALE



E **SUPPORT PIPE OVER LAP**
SCALE: HALF SCALE



G **SUPPORT PIPE AT DOUBLE JAMB**
SCALE: HALF SCALE

F **SUPPORT PIPE AT JAMB**
SCALE: HALF SCALE

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 04-1020.01
Expiration Date 03/15/2012
By Helmut A. Knezevich
Miami Date Product Control
Division

Thornton Tomasetti
330 N. Andrews Ave., Suite 450 • Ft. Lauderdale, FL 33301
T 954-522-3690 • F 954-522-3691 • COA # 7519
Website: www.thorntontomasetti.com
Copyright © 2007 Thornton Tomasetti, Inc.


Poma Corporation
9040 Belvedere Road
West Palm Beach, FL 33411
Tel: (561) 790-5799 • Fax (561) 792-9281

J.W. Knezevich
Professional Engineer
FL License No.: PE 0041961


FEB 07 2007

no.	date	by	description
0	02/07/2007	NW	PREVIOUS DRAWING NO. 99-262

date	02/07/2007
scale	AS NOTED
drawn by	MCR
design by	NW
checked by	VJK
drawing no.	07-301
sheet	2 of 3




H SIDE JAMB "Z" BAR DETAIL
SCALE: HALF SCALE



J LOUVER TO JAMB DETAIL
SCALE: HALF SCALE

N DOUBLE JAMB TO "H" TUBE
DETAIL (CLOSED POSITION)
SCALE: HALF SCALE




K JAMB TO "H" TUBE
BOTTOM DETAIL (CLOSED POSITION)
SCALE: HALF SCALE

NOTE:
KEYHOLE ACCEPTABLE IN ALL BUT
ONE HOLE. PROVIDE ONE 5/16" ϕ
ROUND HOLE FOR FASTENING,
TYPICAL ALL Z BARS.

L DOUBLE JAMB TO "H" TUBE
BOTTOM DETAIL (CLOSED POSITION)
SCALE: HALF SCALE

MAX DESIGN LOAD FOR DETAIL **L** IS 62 P.S.F.
FOR LOADS ABOVE 62 P.S.F. UP TO 97 P.S.F. SEE DETAIL **N**



M TYPICAL "Z" BAR
WALL MOUNT DETAIL (CLOSED POSITION)
SCALE: HALF SCALE

PRODUCT REVISED
as complying with the Florida
Building Code
Acceptance No. 02-1020-01
Expiration Date 03/15/2012
By *Helmut A. Knezevich*
Miami Dade Product Control
Division

BAHAMA SHUTTER

poma Poma Corporation
9040 Belvedere Road
West Palm Beach, FL 33411
Tel: (561) 790-5799 • Fax (561) 792-9281

J.W. Knezevich
Professional Engineer
FL License No.: PE 0041961

FEB 07 2007

revisions	description	date	by
no.	date	no.	description
0	02/07/2007	NW	

date 02/07/2007
Scale AS NOTED drawn by MCR
design by NW checked by VJK
drawing no. 07-301
sheet 3 of 3

Thornton Tomasetti
330 N. Andrews Ave., Suite 450 • Ft. Lauderdale, FL 33301
T 954.522.3690 • F 954.522.3691 • COA # 7519
Website: www.ThorntonTomasetti.com
Copyright © 2007 Thornton Tomasetti, Inc.